

BID 9460.2

Questions and answers

We currently maintain five 1,500-gallon def tanks that are supplied through bulk deliveries. In addition, we have one 1,300-gallon Titan tank located at the Shady Grove Fuel Station and one 650-gallon tank at the Randolph Fuel Station.

PC12

Beginning in 2027, due to governmental regulations, OEMs will begin requiring heavy duty engine oils be compliant with PC12. Since the duration of the bid includes months in 2027, we recommend the contract require that heavy duty engine oils be compliant with PC12 regulations.

Products

I would appreciate further grade or technical specifications on the following products:

1	Antifreeze Case (6/1 gal jugs/case)
2	Antifreeze (Bulk 100 - 250 gals)

Can you provide any further technical specifications for items 1 and 2? **The antifreeze/coolant shall be a Green Extended Life Coolant (ELC) suitable for heavy-duty applications. The coolant must pass the John Deere Cavitation Test (ASTM D7583) and provide protection against liner pitting and cavitation erosion in diesel engines.**

3	Antifreeze Prestone Command 50/50 ELC BULK
4	Antifreeze Prestone Command 50/50 ELC DRUM
5	Precharge Antifreeze 50/50 ELC BULK
6	Precharge Antifreeze 50/50 ELC DRUM

In the above subsection it appears items 5 and 6 are duplicates of items 3 and 4, can you confirm? **Line Items 3,4 are brand specific Prestone Command, Line items 5,6 are not brand specific that is the difference.**

12	Fuel Synthetic Motor Oil - 55 gal drum
----	--

Can you provide the grade of the oil for item no 12? **Item No. 12 – Fuel Synthetic Motor Oil (55-gallon drums): The full synthetic motor oil under Section IV is available in the following SAE viscosity grades: 0W-20, 0W-40, 5W-20, 5W-30, and 5W-40. All grades are full synthetic and meet applicable industry and OEM performance standards.**

110	55 Gallon 1 Drum
-----	------------------

Can you more details for item no 110? If this is a lubricant please provide grade and necessary specs. If this is an empty drum please confirm. **This item is hydraulic oil supplied in 55-gallon drums in the following grades: AW 32, AW 46, AW 68, and AW 150. All grades are anti-wear hydraulic fluids meeting standard industry and OEM specifications.**

111	ISO Grade #32AW,46AW Bulk (150-gallon minimum order quantity)
112	ISO Grade #32AW,46AW Bulk (500-gallon minimum order quantity)
113	ISO Grade EAL #32AW,46AW Drum

Can you please clarify which grade of hydraulic oil you all are looking for in items no 111-113?
Would this be an AW32 or an AW46? **Items No. 111–113 – Hydraulic Oil (ISO AW Grades):**

The hydraulic oil required under these items is available in both ISO AW 32 and ISO AW 46 grades.

Either grade may be supplied based on equipment/application requirements and end-user preference.

- **Item 111: Bulk (150-gallon minimum order) – AW 32 or AW 46**
- **Item 112: Bulk (500-gallon minimum order) – AW 32 or AW 46**
- **Item 113: Drums (EAL hydraulic oil) – AW 32 or AW 46 (as applicable for EAL formulation)**